

# MotionBLITZ® Cube5

## Sensitive High-Speed Recording Camera

### Extremely Fast with Supreme Light Efficiency

Mikrotron MotionBLITZ® Cube5 is the latest of Mikrotron's Cube High-Speed Recording camera family, developed to face high-speed requirements by cutting edge camera technology. Up to 5,000 fps are capable at the camera's 512(H) x 512(V) resolution, however increasable to impressing 195,000 fps by reduction of the Region of Interest (RoI). However, light is not an issue: the Cube's light sensitivity of 1,000 / 800 ASA (monochrome / color) enables invaluable high speed recordings even in less illuminated applications.

#### Recording with History Function

The MotionBLITZ® Cube5 onboard ring buffer allows buffering of triggered events up to 3 seconds at full resolution and speed (extended buffer option). The history function allows pre and post event recording through free selection of frames or recording time. The optional available ImageBLITZ® Auto Trigger even goes a step further: it allows object generated triggering directly through the camera by a selectable section of the RoI used as sensor.

#### Maximum Performance at Minimum Form Factor

The MotionBLITZ® Cube5 comes up with the smallest form factor ever for a high speed recording camera at this capacity. A housing depth of appx. 92mm (C-Mount version) allows the MotionBLITZ® Cube5 to be utilized in an unrivalled manner even in cramped space conditions.



#### GigE Vision: Absolute Flexibility at High Transfer Rates

The MotionBLITZ® Cube5 Gigabit-Ethernet interface allows camera operation from any standard PC or Notebook at highest transfer rates. Provided with a ruggedized Phoenix industrial plug, the Cube5 is designed for operation under real industrial conditions. Based on innovative GigE Vision communication standard, the Cube5 enables a multiplicity of image processing software to be frictionless attached.

#### A Great Variety of Extension Options

Get exactly the camera you need: MotionBLITZ® Cube5 offers a multiple range of optional all-purpose extensions. Many options from ring buffer upgrade to ImageBLITZ® Auto Trigger or multi sequence recording are available. The optional integrated F-Mount Lens mount provides a much larger field of view which results in an evenly exposed image. Even a Hi-G-Version is available.

- **1,000 / 800 ASA Light Sensitivity**
- **Up to 5,000 fps\* at 512(H) x 512(V) Resolution**
- **Up to 195,000 fps by Infinitely Variable RoI**
- **Smallest Form Factor, Minimal Housing Depth**
- **GigE Vision Interface with Phoenix Industrial Plug**
- **Battery Pack for up to 1 h Operating**
- **Power Down Mode for 8h Data Retention**
- **Multisequence Recording**
- **ImageBLITZ® Auto Trigger**
- **Memory Extension**
- **Shock and Vibration Proof Version Available**
- **IRIG-B Frame Synchronisation**

\*fps (frames per second)

# MotionBLITZ® Cube5

## Sensitive High-Speed Recording Camera

### Technical Data

<b>Light Sensitivity</b>	1,000 ASA monochrome 800 ASA color
<b>Sensor</b>	Fast CMOS Sensor, 512(H) x 512(V) pixel 8-bit monochrome or RGB color with BAYER filter
<b>Pixel Size</b>	16 x 16 µm
<b>Sensor Sensitivity (monochrome)</b>	9V/lux-Sec. bei 550nm
<b>Frame Speed</b>	28 - 5,000 fps* @ full 512 (H) x 512 (V) resolution Up to 195,000 fps* with reduced resolution
<b>Recording Time</b>	1.5 sec. @ full resolution & 5,000 fps Extended recording times at reduced resolution and/or image speed
<b>Shutter</b>	Global Electronic Shutter from 2µsec to 1/ frame rate
<b>Internal Dynamics</b>	59 dB
<b>Spectral Bandwidth</b>	400 – 800 nm
<b>System Design</b>	Modular, scalable and network-compatible concept, standard PC or notebook Synchronous processing of multiple cameras
<b>Camera Size</b>	93 (B) x 69 (H) x 92 (T) mm (C-Mount) 93 (B) x 69 (H) x 128 (T) mm (F-Mount)
<b>Weight</b>	900g, without lens
<b>Environment</b>	+5...45° C, (41-113°F)
<b>Battery Capacity</b>	Recording mode: 1h; standby mode: 1.5 hours; Power Down mode 8 h
<b>Lens Mount</b>	C-Mount; F-Mount (option)
<b>Power Supply</b>	10,5 - 24V DC external power supply and internal rechargeable battery
<b>Power Consumption</b>	15W max
<b>Software</b>	MotionBLITZ® operating software for Windows 2000/XP™
<b>Frame Storage</b>	BMP and AVI format
<b>Camera-PC Interface</b>	1000/100 Ethernet Interface (Gigabit Ethernet)
<b>Triggerung / Synchronisation</b>	Ext. Trigger, ImageBLITZ / Sync.-Input on the camera (opto coupled)
<b>Synchronisation</b>	TTL-Sync. Output (opto coupled)
<b>Analog Input</b>	5V (8-Bit) (opto coupled)
<b>Digital Input</b>	4 Bit (TLL) (opto coupled)

\*fps (frames per second)

### Optional Extensions

Extended recording time up to 3 sec recording time @ full resolution & speed	ImageBLITZ® Auto Trigger	Multi sequence recording	F-Mount	Hi-G 100g Shock 100g / 25 msec Vibration 10g	Industrial Standard Phoenix Interface Plug	IRIG B Synchronisation
--	-----------------------------	--------------------------------	---------	--	---	---------------------------

### Recording Data

Resolution	Frame Rate	Resolution	Frame Rate
512(H) x 512(V)	5,000 fps*	512(H) x 64(V)	40,000 fps*
512(H) x 256(V)	10,000 fps*	512(H) x 28(V)	80,000 fps*
512(H) x 128(V)	20,000 fps*	512(H) x 10(V)	195,000 fps*

All brand and product names which appear in this document may be trademarks or registered trademarks of the corresponding companies. We reserved the right to change specification without notification.